



STAVE

PLANK

CEILING



CREDENCE

We The Trust



BENEFITS

- Highly Aesthetic & decorative
- Humidity & fire resistant
- Durable & easy installation

AREA OF APPLICATION

- Airports, Convention Centers
- Cultural Centers, Industrial Space, Offices
- Malls

TECHNICAL DATA SHEET




HUMIDITY RESISTANCE



EASY TO CLEAN



MULTIPLE COLOUR RANGE



RECYCLABLE



FIRE RETARDANT

TECHNICAL DATA SHEET

Finish	Powder Coated/Coil coated
Shapes	Plank
Thickness	0.5 mm Aluminum
Colour	White / *As per RAL (Powder coated 60 microns)
Size	184x12.5 mm ($\pm 10\%$)
Flange	23.9 mm
Light Reflectance	> 90%
Humidity Resistance	RH 99%
Fire Resistance	Class 1 BS476 (part 6 & 7)

*PLEASE CONTACT TO CREDENCE SALES REPRESENTATIVE FOR SIZE & COLOUR OF REQUIRED SHAPES

COLOUR OPTIONS



WHITE /* AS PER RAL STANDARD

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATION OF 184 C ALUMINUM POWDER COATED WHITE PANEL WITH SYSTEM



184 C CEILING SYSTEM COMPRISES OF 184 MM X 12.5 MM \pm 10% PANELS WITH 23.9 MM FLANGE ROLL FORMED OUT OF 0.50 MM THICK ALUM. COILS. PANELS SHALL BE POWDER COATED WITH 60 MICRONS POLYESTER PAINT COATING ON FRONT SIDE ONLY. PANELS ARE FIXED ON TO ROLL FORMED CARRIERS 32 MM WIDE X 39 MM DEEP OUT OF 0.50 MM G.I SHEET WITH CUTOUTS TO HOLD THE PANELS IN MODULE OF 200 MM AT MAXIMUM 1.2 MTR C/C WITHOUT INSULATION AND AT MAXIMUM 1MTR C/C WITH INSULATION. CARRIERS ARE SUSPENDED FROM THE ROOF OR TRUSS BY 4 MM DIA. GALVANIZED STEEL SUSPENSION WIRE ROD HANGER WITH SPECIAL HEIGHT ADJUSTMENT SUSPENSION CLIP AT MAX. 1.2 MTR C/C. HANGERS ARE FIXED TO THE ROOF BY 'J' HOOKS OR CEILING BRACKETS AND NYLON INSERTS. PANELS ARE FACTORY CUT IN LENGTHS UP TO MAXIMUM 5 M TO SUIT SITE DIMENSIONS OR SHOP DRAWINGS. G.I EDGE PROFILES OR WALL ANGLES ARE 24 MM X 24 MM X 0.4 MM THICK AND MATCH THE COLOUR OF THE PANEL.

MAINTENANCE

THE MAINTENANCE INSTRUCTION & RECOMMENDATIONS TO REMOVE DUST, PEN MARKS, STAINS ARE AS FOLLOWS –

- ✓ USE SMOOTH BRUSH OR VACUUM CLEANER FOR ANY TYPE OF DUST OR DIRT PARTICLES. ENSURE TO CLEAN IN ONE DIRECTION ONLY.
- ✓ USE FRESH GOOD QUALITY CLEANER FOR REMOVING PEN MARKS OR SMUDGES. ENSURE TO CLEAN IN ONE DIRECTION ONLY.
- ✓ USE VOLATILE SOLVENT BASED CLEANER FOR OIL BASED STAINS. ENSURE TO CLEAN IN ONE DIRECTION ONLY

WARRANTY

✓ 5 YEARS WARRANTY FOR CREDENCE STAVE PANEL

* PLEASE REFER TO WARRANTY DOSSIER FOR WARRANTY CLAUSES & TERMS

CONTACT US

Call us: +91-120-5105463
+91-99900 49959

Email: info@credenceindustries.com , sales@credenceindustries.com

