

NIMBUS - TECHNICAL DATA



ACOUSTIC
PERFORMANCE




EASY TO CLEAN



HUMIDITY RESISTANCE



COLOUR OPTION



RECYCLABLE



FIRE RETARDANT

Finish	Powder coated / Pre Coated
Size	600x600 mm, 600x1200 mm
Thickness	0.5 in Galvanized Iron, 0.7 in Aluminium, 0.5 in SS
Colour	Global White / *As per RAL Standards
NRC	0.5 – 0.7 *
Perforation	1.8 mm, 2.5 mm (* Custom perforation available)
Light Reflectance	>0.85%
Humidity Resistance	RH 99%
Hygiene	Anti Bacterial/Anti fungal/antimicrobial coating available

*MINIMUM 1.8 MM DIA PERFORATED GLIP IN METAL TILE WITH ACOUSTIC FLEECE HAS NRC 0.5, TO ENHANCE THE ACOUSTIC & NRC: SUGGESTIVE METHOD TO HAVE A LAYER OF APPORTIONS WOOL ON TILE OR CONTACT TO CREDENCE ACOUSTIC EXPERTS

COLOUR OPTIONS

WHITE/ * AS PER RAL STANDARD



*FOR RAL SHADES MOQ IS 500 SQM